



# **Product Datasheet**

19 Wall Recessed & Inground>Indoor/Outdoor Dark Light Wall Recessed

68032/AL/W



3W LED recessed wall light, IP54, ideal for, indoor and outdoor, corridors and stairs illumination.

Complete with driver.

Supplied with box for concrete installation

Complies with standard EN60598-1 and any other specific standards.



Downloads










Dimensions



#### Gallery




#### **Physical Specification**

Item Group	19 Wall Recessed & Inground
Family	Indoor/Outdoor Dark Light Wall Recessed
Order Code	68032/AL/W
Colour	Aluminium
Material	Natural Aluminium
Shape	Rectangular
Length	70mm

Width	70mm
Height	45mm
Cutout Hole Diameter	52mm
Recessed wall	Yes
Depth Required	110mm Concrete 50mm Gypsum
Indoor	Yes
Outdoor	Yes
Adjustable	No
Electrical Characteristics	
Gear	Built In
Eitting L Driver	
Fitting + Driver	
Input Voltage	100-240V
50 Hz	Yes
60 Hz	Yes
Safety Class	
Power(Watts)	3W
IP Rating	IP54
Light Source	LED built in
Dimmable	No
F Mark	F
Fitting	
Input Type	Constant Current
Input Current	700mA
Voltage	4V
Safety Class	<u></u>
Power(Watts)	2,8W
IP Rating	IP54
Light Source	LED built in

LED Brand	Cree
F Mark	F
Gear	
Gear Type	Led Driver
Input Voltage	100-240V
50 Hz	Yes
60 Hz	Yes
Power(Watts)	2,8-3,5W
Power Factor	0,5
Constant Current	Yes
700mA	4-5V
IP Rating	IP20
Safety Class	
Brand	HEP
Protection	0
Illumination Data	
Colour Temperature	3000K
Illumination Diagram	
Dark Light	Yes
Packing Info	
Box Length	11cm
Box Width	7,5cm
Box Height	7,5cm
DOX FROIGHT	7,00111
Box Weight	
Box Weight Pcs/Carton	0,3Kg
Pcs/Carton	0,3Kg 30
	0,3Kg

## Energy Label



### Certification & Warranty

Warranty	2 Years
Weee Directive	Yes

one

switch to one light!

