



Product Datasheet

15 Plafo>The LED Panel Plafo Round

62115F/W/C



16W LED slim plafo light, IP40, suitable for residential and commercial application.

Supplied with non-dimmable LED driver.

Complies with standard EN60598-1 and any other specific standards.



Downloads









Dimensions



____ 39mm

Gallery




Physical Specification

15 Plafo
The LED Panel Plafo Round
62115F/W/C
White
Die Cast
Circular
39mm

Diameter	240mm
Surface Ceiling	Yes
Indoor	Yes
Adjustable	No
lectrical Characteristics	
Gear	External-Included
Fitting + Driver	
Input Voltage	220-240V
50 Hz	Yes
60 Hz	Yes
Safety Class	
Power(Watts)	16W
IP Rating	IP40
Light Source	LED built in
Dimmable	No
F Mark	F
Fitting	
Input Type	Constant Current
Input Current	500mA
Voltage	28V
Safety Class	<u> </u>
Power(Watts)	14W
IP Rating	IP40
Light Source	LED built in
LED Type	SMD 2016
LED Brand	Sanan
F Mark	F

Colour Temperature Lumen Output Light Efficiency CRI B0 Illumination Diagram	Gear	
Sol Hz	Gear Type	Led Driver
Power (Watts) 12-14W 12	Input Voltage	220-240V
Power (Watts) 12-14W Power Factor 0,9 Constant Current Yes 500mA 24-28V IP Rating IP20 Safety Class □ Dimmable No Housing Material Plastic Output Terminal Cable Brand KEGU Illumination Data KEGU Colour Temperature 4000K Lumen Output 1118im Light Efficiency 70im/W CRI 80 Illumination Diagram Illumination Diagram Packing Info 25,5cm Box Weight 4,5cm Box Weight 1,2kg Pcs/Carton 10	50 Hz	Yes
Power Factor 0,9 Constant Current Yes 500mA 24-28V IP Rating IP20 Safety Class □ Dimmable No Housing Material Plastic Output Terminal Cable Brand KEGU Illumination Data KEGU Colour Temperature 4000K Lumen Output 1118Im Light Efficiency 70Im/W CRI 80 Illumination Diagram Illumination Diagram Packing Info 25,5cm Box Length 24,5cm Box Weight 4,5cm Box Weight 1,2kg Pes/Carton 10	60 Hz	Yes
Constant Current Yes 500mA 24-28V IP Rating IP20 Safety Class □ Dimmable No Housing Material Plastic Output Terminal Cable Brand KEGU Colour Temperature 4000K Lumen Output 1118 Im Light Efficiency 70im/W CRI 80 Illumination Diagram Packing Info Box Length 8x Length 25,5cm Box Width 4,5cm Box Weight 1,2kg Pes/Carton 10	Power(Watts)	12-14W
### Space	Power Factor	0,9
IP Rating IP20 Safety Class	Constant Current	Yes
Safety Class □ Dimmable No Housing Material Plastic Output Terminal Cable Brand KEGU Illumination Data 4000K Lumen Output 1118lm Light Efficiency 70lm/W CRI 80 Illumination Diagram Illumination Diagram Packing Info 25,5cm Box Length 24,5cm Box Width 4,5cm Box Height 4,5cm Box Weight 1,2kg Pcs/Carton 10	500mA	24-28V
Dimmable No Housing Material Plastic Output Terminal Cable Brand KEGU Illumination Data 4000K Lumen Output 1118lm Light Efficiency 70lm/W CRI 80 Illumination Diagram Assert Langth Box Length 25,5cm Box Width 24,5cm Box Height 4,5cm Box Weight 1,2kg Pes/Carton 10	IP Rating	IP20
Housing Material Cutput Terminal Brand KEGU Colour Temperature Colour Temperature Lught Efficiency CRI Blumination Diagram Packing Info Box Length Box Width Box Weight Box Weight Box Weight Box Weight 1,2kg Pcs/Carton Packing Info 10	Safety Class	
Output Terminal Cable Brand KEGU Illumination Data Colour Temperature 4000K Lumen Output 1118lm Light Efficiency 70lm/W CRI 80 Illumination Diagram A Packing Info 25,5cm Box Wridth 24,5cm Box Height 4,5cm Box Weight 1,2kg Pcs/Carton 10	Dimmable	No
Brand KEGU Illumination Data Colour Temperature 4000K Lumen Output 1118Im Light Efficiency 70Im/W CRI 80 Illumination Diagram Packing Info Box Length 25,5cm Box Width 24,5cm Box Height 4,5cm Box Weight 1,2kg Pcs/Carton 10	Housing Material	Plastic
Colour Temperature 4000K Lumen Output 1118Im Light Efficiency 70Im/W CRI 80 Illumination Diagram Packing Info Box Length 25,5cm Box Width 24,5cm Box Height 4,5cm Box Weight 1,2kg Pcs/Carton 10	Output Terminal	Cable
Colour Temperature 4000K Lumen Output 1118lm Light Efficiency 70lm/W CRI 80 Illumination Diagram Illumination Diagram Packing Info 25,5cm Box Length 24,5cm Box Width 24,5cm Box Height 4,5cm Box Weight 1,2kg Pcs/Carton 10	Brand	KEGU
Colour Temperature 4000K Lumen Output 1118lm Light Efficiency 70lm/W CRI 80 Illumination Diagram Illumination Diagram Packing Info 25,5cm Box Length 24,5cm Box Width 24,5cm Box Height 4,5cm Box Weight 1,2kg Pcs/Carton 10		
Lumen Output 1118lm Light Efficiency 70lm/W CRI 80 Illumination Diagram Illumination Diagram Packing Info Box Length Box Width 24,5cm Box Weight 4,5cm Box Weight 1,2kg Pcs/Carton 10	Illumination Data	
Lumen Output 1118lm Light Efficiency 70lm/W CRI 80 Illumination Diagram Illumination Diagram Packing Info Box Length Box Width 24,5cm Box Weight 4,5cm Box Weight 1,2kg Pcs/Carton 10	Colour Toron areture	40001/
Light Efficiency 70lm/W CRI 80 Illumination Diagram		
CRI 80 Illumination Diagram Illumination Diagram Packing Info 25,5cm Box Length 24,5cm Box Width 24,5cm Box Height 4,5cm Box Weight 1,2kg Pcs/Carton 10		
Box Length 25,5cm Box Width 24,5cm Box Height 4,5cm Box Weight 1,2kg Pcs/Carton 10		
Packing Info Box Length 25,5cm Box Width 24,5cm Box Height 4,5cm Box Weight 1,2kg Pcs/Carton 10		
Box Length 25,5cm Box Width 24,5cm Box Height 4,5cm Box Weight 1,2kg Pcs/Carton 10		
Box Length 25,5cm Box Width 24,5cm Box Height 4,5cm Box Weight 1,2kg Pcs/Carton 10		
Box Width24,5cmBox Height4,5cmBox Weight1,2kgPcs/Carton10	Packing Info	
Box Height4,5cmBox Weight1,2kgPcs/Carton10	Box Length	25,5cm
Box Weight 1,2kg Pcs/Carton 10	Box Width	24,5cm
Pcs/Carton 10	Box Height	4,5cm
Barcode 5291889039969	Box Weight	
		1,2kg

Energy Label



Certification & Warranty

Warranty 2 Years

Weee Directive Yes

switch to one light!

