



Product Datasheet

15 Plafo>The LED Panel Plafo Round

62115F/W/W



16W LED slim plafo light, IP40, suitable for residential and commercial application.

Supplied with non-dimmable LED driver.

Complies with standard EN60598-1 and any other specific standards.



Downloads









Dimensions



_ 39mm

Gallery




Physical Specification

Item Group	15 Plafo
Family	The LED Panel Plafo Round
Order Code	62115F/W/W
Colour	White
Material	Die Cast
Shape	Circular
Height	39mm

Diameter	240mm
Surface Ceiling	Yes
Indoor	Yes
Adjustable	No
lectrical Characteristics	
Gear	External-Included
Fitting + Driver	
Input Voltage	220-240V
50 Hz	Yes
60 Hz	Yes
Safety Class	
Power(Watts)	16W
IP Rating	IP40
Light Source	LED built in
Dimmable	No
F Mark	F
Fitting	
Input Type	Constant Current
Input Current	500mA
Voltage	28V
Safety Class	
Power(Watts)	14W
IP Rating	IP40
Light Source	LED built in
LED Type	SMD 2016
LED Brand	Sanan
F Mark	F

Cear Type Led Driver Input Voltage 220-240V 50 Hz Yes 80 Hz Yes Power Ractor 0,9 Constant Current Yes 500mA 24-28V IP Rating IP 20 Safety Class □ Dimmable No Housing Material Pleasto Output Terminal Cable Brand KEGU Illumination Data 1006im Lumen Output 1006im Light Efficiency 67.06im/W CRI 80 Illumination Diagram 25.5cm Box Length 24.5cm Box Weight 4,5cm Box Weight 1,2kg PoskCaton 10 Brackde 6201888036886	Gear	
Solid Power Pow	Gear Type	Led Driver
Power(Watts) 12-14W 12-	Input Voltage	220-240V
Power (Watts) 12-14W Power Factor 0,9 Constant Current Yes 500mA 24-28V IP Rating IP20 Safety Class □ Dimmable No Housing Material Plastic Output Terminal Cable Brand KEGU Illumination Data KEGU Colour Temperature 3000K Lumen Output 1006im Light Efficiency 67,06im/W CRI 80 Illumination Diagram Illumination Diagram Packing Info 25,5cm Box Width 24,5cm Box Height 4,5cm Box Weight 1,2kg Pcs/Carton 10	50 Hz	Yes
Power Factor 0,9 Constant Current Yes 500mA 24-28V IP Rating IP20 Safety Class □ Dimmable No Housing Material Plastic Output Terminal Cable Brand KEGU Illumination Data KEGU Colour Temperature 3000K Lumen Output 1006im Light Efficiency 67.06im/W CRI 80 Illumination Diagram Illumination Diagram Pasking Info 25.5cm Box Length 24.5cm Box Weight 4.5cm Box Weight 1,2kg Pcs/Carton 10	60 Hz	Yes
Constant Current Yes 500mA 24-28V IP Rating IP20 Safety Class □ Dimmable No Housing Material Plastic Output Terminal Cable Brand KEGU Illumination Data Colour Temperature Lumen Output 1006im Light Efficiency 67,06im/W CRI 80 Illumination Diagram A Peacking Info 25,5cm Box Weight 24,5cm Box Weight 1,2kg PostCarton 10	Power(Watts)	12-14W
24-28V IP Rating	Power Factor	0,9
IP Rating	Constant Current	Yes
Safety Class □ Dimmable No Housing Material Plastic Output Terminal Cable Brand KEGU Illumination Data Colour Temperature Lumen Output 1006lm Light Efficiency 67,06lm/W CRI 80 Illumination Diagram Illumination Diagram Packing Info 25,5cm Box Length 24,5cm Box Width 4,5cm Box Height 4,5cm Box Weight 1,2kg Pes/Carton 10	500mA	24-28V
Dimmable	IP Rating	IP20
Housing Material	Safety Class	
Output Terminal Cable Brand KEGU Illumination Data Colour Temperature 3000K Lumen Output 1006lm Light Efficiency 67,06lm/W CRI 80 Illumination Diagram A Packing Info 25,5cm Box Length 24,5cm Box Width 4,5cm Box Height 1,2kg Pcs/Carton 10	Dimmable	No
Brand KEGU	Housing Material	Plastic
Colour Temperature 3000K Lumen Output 1006lm Light Efficiency 67,06lm/W CRI 80 Illumination Diagram	Output Terminal	Cable
Colour Temperature 3000K Lumen Output 1006lm Light Efficiency 67,06lm/W CRI 80 Illumination Diagram	Brand	KEGU
Colour Temperature 3000K Lumen Output 1006lm Light Efficiency 67,06lm/W CRI 80 Illumination Diagram		
Lumen Output 1006lm Light Efficiency 67,06lm/W CRI 80 Illumination Diagram Illumination Diagram Packing Info Box Length Box Width 24,5cm Box Weight 4,5cm Box Weight 1,2kg Pcs/Carton 10	Illumination Data	
Lumen Output 1006lm Light Efficiency 67,06lm/W CRI 80 Illumination Diagram Illumination Diagram Packing Info Box Length Box Width 24,5cm Box Weight 4,5cm Box Weight 1,2kg Pcs/Carton 10	Colour Toron arcture	200014
Light Efficiency 67,06Im/W CRI 80 Illumination Diagram A Packing Info Box Length Box Width 24,5cm Box Weight 4,5cm Box Weight 1,2kg Pcs/Carton 10		
CRI 80 Illumination Diagram Illumination Diagram Packing Info Box Length 25,5cm Box Width 24,5cm Box Height 4,5cm Box Weight 1,2kg Pcs/Carton 10		
Box Length 25,5cm Box Width 24,5cm Box Height 4,5cm Box Weight 1,2kg Pcs/Carton 10		
Packing Info Box Length 25,5cm Box Width 24,5cm Box Height 4,5cm Box Weight 1,2kg Pcs/Carton 10		
Box Length 25,5cm Box Width 24,5cm Box Height 4,5cm Box Weight 1,2kg Pcs/Carton 10		
Box Length 25,5cm Box Width 24,5cm Box Height 4,5cm Box Weight 1,2kg Pcs/Carton 10		
Box Width24,5cmBox Height4,5cmBox Weight1,2kgPcs/Carton10	Docking Info	
Box Height4,5cmBox Weight1,2kgPcs/Carton10	Packing into	
Box Weight 1,2kg Pcs/Carton 10		25,5cm
Pcs/Carton 10	Box Length	
	Box Length Box Width	24,5cm
Barcode 5291889035886	Box Length Box Width Box Height	24,5cm 4,5cm
	Box Length Box Width Box Height Box Weight	24,5cm 4,5cm 1,2kg

Energy Label



Certification & Warranty

Warranty 2 Years

Weee Directive Yes

switch to one light!

